

Certificate of Compliance

Certificate Number:

UL-US-2429359-0

Report Reference:

E537819-20240726

Issue Date:

2024-07-26

Issued to:

Zhejiang Hengtuo electronic Technology Co., LTD
298 Yongqing Road, Bridge Town, Nanhui District Jiaxing,
Zhejiang 314000
China

This certificate confirms that representative samples of:

FPQU2 - Optical Isolators - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 1577, Edition 5, Issue Date 2014-04-25, Revision Date 2023-07-06

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



David Piecuch
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2429359-0
Report reference ES37819-20240726
Date 2024-07-26

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

| Model | Product Description |
|--|---|
| HT-10XX, where "X" maybe any alphanumeric character or blank. | Double protection optical isolators at 5000 Vac isolation voltage |
| HT-302X, where "X" maybe any alphanumeric character or blank. | Double protection optical isolators at 5000 Vac isolation voltage |
| HT-304X, where "X" maybe any alphanumeric character or blank. | Double protection optical isolators at 5000 Vac isolation voltage |
| HT-305X, where "X" maybe any alphanumeric character or blank. | Double protection optical isolators at 5000 Vac isolation voltage |
| HT-306X, where "X" maybe any alphanumeric character or blank. | Double protection optical isolators at 5000 Vac isolation voltage |
| HT-307X, where "X" maybe any alphanumeric character or blank. | Double protection optical isolators at 5000 Vac isolation voltage |
| HT-308X, where "X" maybe any alphanumeric character or blank. | Double protection optical isolators at 5000 Vac isolation voltage |
| HT-31XX, where "X" maybe any alphanumeric character or blank. | Double protection optical isolators at 5000 Vac isolation voltage |
| HT-6N13X, where "X" maybe any alphanumeric character or blank. | Double protection optical isolators at 5000 Vac isolation voltage |
| HT-X213, where "X" maybe any alphanumeric character or blank. | Double protection optical isolators at 5000 Vac isolation voltage |
| HT-X223, where "X" maybe any alphanumeric character or blank. | Double protection optical isolators at 5000 Vac isolation voltage |
| HT6-2XX, where "X" maybe any alphanumeric character or blank. | Double protection optical isolators at 5000 Vac isolation voltage |
| HTM-4XX, where "X" maybe any alphanumeric character or blank. | Double protection optical isolators at 3750 Vac isolation voltage |
| HTM-5XX, where "X" maybe any alphanumeric character or blank. | Double protection optical isolators at 3750 Vac isolation voltage |
| HTM-6XX, where "X" maybe any alphanumeric character or blank. | Double protection optical isolators at 3750 Vac isolation voltage |
| HTM-8XX, where "X" maybe any alphanumeric character or blank. | Double protection optical isolators at 3750 Vac isolation voltage |



David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>



Solutions